

# SAFETY DATA SHEET



1000 Tedia Way  
Fairfield, Ohio 45014  
USA  
Email: [tedia@tedia.com](mailto:tedia@tedia.com)  
Web: [www.tedia.com](http://www.tedia.com)

**24-Hour Emergency Number (CHEMTREC)**

USA: 800-424-9300

International: 703-527-3887

**All non-emergency numbers should be directed  
to Customer Service at 800-PURITY1**

## DIBUTYLAMINE

**SDS No. M0057**

### 1. CHEMICAL PRODUCT AND COMPANY IDENTIFICATION

Product Name: Dibutylamine

Synonyms: n-Butyl-1-butanamine; Di-n-butylamine

Recommended Use: This product is recommended for laboratory and manufacturing use only. It is not recommended for drug, food or household use.

### 2. HAZARDS IDENTIFICATION



**Classification:**

Flammable Liquids: GHS Category 3

Acute Toxicity, Oral: GHS Category 3

Acute Toxicity, Dermal: GHS Category 4

Skin Corrosion: GHS Category 1B

Eye Damage: GHS Category 1

**Label Elements**

Signal Word: DANGER!

Hazard Statements:

H226 – Flammable liquid and vapor.

H302 – Harmful if swallowed.

H314 – Causes severe skin burns and eye damage.

H332 – Harmful if inhaled.

Precautionary Statements:

P210 – Keep away from heat/sparks/open flames/hot surfaces. – No smoking.

P280 – Wear protective gloves/protective clothing/eye protection/face protection.

P301+P310 – If SWALLOWED: Immediately call or POISON CENTER or a doctor/physician.

P303+P361+P353 – If on skin or hair: Remove/take off immediately all contaminated clothing. Rinse skin with water/shower.

**Emergency Overview**

Corrosive. Causes burns to any area of contact. Harmful if swallowed, inhaled, or absorbed through the skin. Flammable liquid and vapor. Target Organs: Eyes, skin, respiratory tract, digestive tract, and mucous membranes.

Clear focus. Consistent results. Complete confidence.

HMIS Rating:

Health – 3 Flammability – 2 Physical Hazard – 0 PPE – User supplied

NOTE: HMIS ratings use a numbering scale that ranges from 0 - 4 to indicate the degree of hazard. A value of zero means the chemical presents no hazard while a value of four indicates a high hazard. These ratings are based on the inherent properties of this chemical under expected conditions of normal use and are not intended to be used in emergency situations. PPE is determined by the user based on their needs and conditions.

**3. COMPOSITION AND INFORMATION ON INGREDIENTS**

<u>Ingredient</u>	<u>CAS No</u>	<u>Percent</u>	<u>Hazardous</u>
Dibutylamine	111-92-2	>99%	Yes

**4. FIRST-AID MEASURES**

Inhalation: If inhaled, remove to fresh air. If breathing is labored or with coughing, give oxygen. If not breathing, begin artificial respiration, but DO NOT give mouth-to-mouth resuscitation. Get medical attention.

Ingestion: If swallowed, get medical attention immediately; DO NOT induce vomiting. Give victim plenty of water. Never give anything by mouth to an unconscious person. If not breathing, begin artificial respiration.

Skin Contact: Immediately flush skin with plenty of water for at least 15 minutes while removing contaminated clothing and shoes. Get medical attention immediately. Wash clothing and shoes before reuse.

Eye Contact: Immediately flush eyes with plenty of water for at least 15 minutes, lifting lower and upper eyelids occasionally. Get medical attention immediately.

Notes to Physician: Treat symptomatically and supportively.

**5. FIRE FIGHTING MEASURES**

Flammability: Flammable liquid and vapor (GHS Category 3)

Auto-ignition Temperature: 312° C (594° F)

Flash Point: 47° C (117° F)

Flammable Limits: Lower Limit – 1.1 vol %, Upper Limit – Not available

Products of Combustion: May decompose into toxic products under fire conditions (nitrogen oxides, carbon monoxide, carbon dioxide, amines).

Specific Fire Hazards: As in any fire, always wear self-contained breathing apparatus in pressure-demand (MSA/NIOSH approved or equivalent), and full protective gear. Use water spray to keep fire exposed containers cool. Approach fire from upwind to avoid hazardous vapors and toxic decomposition products. Vapors may cause flash fire. Vapors are heavier than air and may travel to a source of ignition and flash back. Vapors can spread along the ground and collect in low or confined areas.

Specific Explosion Hazards: Sensitive to static discharge.

Fire Fighting Media: Water spray, dry chemical, alcohol foam, or carbon dioxide. Water spray may be used to keep fire exposed containers cool.

National Fire Protective Association (Estimated): Health - 3, Flammability - 2, Reactivity - 0

NOTE: NFPA ratings use a numbering scale that ranges from 0 - 4 to indicate the degree of hazard. A value of zero means the chemical presents no hazard while a value of four indicates a high hazard. They are for use by emergency personnel to address the hazards that are presented by short term, acute exposure to this product under fire, spill, or similar emergencies. Ratings involve data and interpretations that may vary from company to company.

**6. ACCIDENTAL RELEASE MEASURES**

Absorb spilled liquid with sorbent pads, socks, or other inert material such as vermiculite, sand, or earth. Water can be used to create a non-flammable mixture. Provide ventilation to the affected area and remove all ignition sources. Approach the spill from upwind and pick up absorbed material and place it in a suitable container. Always use proper personal protective equipment as described in section 8.

## 7. HANDLING AND STORAGE

Precautions: Always use proper personal protective equipment as described in section 8. Wash thoroughly after handling. Ground and bond containers when transferring material. Avoid contact with eyes, skin, and clothing. Remove contaminated clothing and wash before reuse. Empty containers contain product residue (liquid and vapor) and can be dangerous. Keep container tightly closed and away from heat, spark, and flame. Do not pressurize, cut, weld, braze, solder, drill, grind, or expose empty containers to heat, sparks, or open flames. Use with adequate ventilation. Avoid breathing vapor or mist.

Storage: Keep in a flammables area away from all sources of ignition and oxidizing materials. Keep in a tightly closed container. Store in a cool, dry, well-ventilated area away from incompatible substances. Keep away from acids. Protect from moisture.

## 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Engineering Controls: Use explosion-proof ventilation equipment. Facilities storing or using the material should be equipped with eyewash station and a safety shower. Use adequate general or local exhaust ventilation to keep airborne concentrations below the permissible exposure limits.

Personal Protection: Wear protective chemical goggles and face shield for eye and face protection. Use appropriate protective gloves and protective clothing to prevent skin exposure. A respiratory protection program that meets OSHA 29 CFR 1910.134 and ANSI Z88.2 requirements or European Standard EN 149 must be followed whenever possible. Always use a NIOSH or European Standard EN 149 approved respirator when necessary.

Exposure Limits:

ACGIH – None

AHIA – WEEL 5ppm, ceiling; skin contact can invalidate ceiling limit.

NIOSH – None

OSHA Final PELs – None

## 9. PHYSICAL AND CHEMICAL PROPERTIES

Physical State and Appearance: Clear, colorless liquid.

Odor: Amine like odor

Molecular Formula:  $[\text{CH}_3(\text{CH}_2)_3]_2\text{NH}$

Molecular Weight: 129.25

Auto-ignition Temperature: 312° C (594° F)

Flash Point: 47° C (117° F)

Flammable Limits: Lower Limit – 1.1 vol %, Upper Limit – Not available

pH: Not available.

Boiling Point: 159° C (318° F) @ 760 mm Hg

Freezing/Melting Point: -60° C (-76° F)

Decomposition Temperature: Not available.

Specific Gravity: 0.76 g/cm<sup>3</sup>

Vapor Density (Air=1): 4.46

Vapor Pressure: 2 mm Hg @ 20° C.

Viscosity: Not available.

Solubility: Soluble in water.

## 10. STABILITY AND REACTIVITY

Stability: Stable under normal temperatures and pressures.

Conditions to Avoid: Ignition sources, excess heat.

Incompatibility With Various Substances: Acids, acid chlorides, acid anhydrides, strong oxidizers, halogenated compounds, hypochlorite and reactive organic compounds.

Hazardous Decomposition Products: Nitrogen oxides, carbon monoxide, carbon dioxide, amines.

Hazardous Polymerization: Will not occur

## 11. TOXICOLOGICAL INFORMATION

Routes of Entry: Inhalation, skin absorption, skin contact

Acute Exposure Hazards:

INHALATION HAZARD: Inhalation produces damaging effects on the mucous membranes and upper respiratory tract. Symptoms may include irritation of the nose and throat, and labored breathing. May cause lung edema, a medical emergency.

INGESTION HAZARD: Corrosive. Toxic, destructive to tissues. May cause sore throat, abdominal spasms, vomiting and diarrhea.

SKIN CONTACT HAZARD: Corrosive. Cause skin burns with much pain. May be absorbed through skin.

EYE CONTACT HAZARD: Corrosive. Vapors irritate the eyes. Splashes may cause eye burns with redness, pain, blurred vision.

Chronic Exposure Hazards: Chronic exposure may produce effects similar to acute exposure.

Animal Toxicity:

Oral, rat: LD50 = 189 mg/kg;

Skin, rabbit: LD50 = 1010 mg/kg;

Carcinogenicity: Not listed as a carcinogen by ACGIH, IARC, NTP, or CA Prop 65

Epidemiology: No information available.

Teratogenicity: No information available.

Reproductive Effects: No information available.

Mutagenicity: No information available.

Neurotoxicity: No information available.

## 12. ECOLOGICAL INFORMATION

Environmental Toxicity: No information available.

Environmental Fate: When released into the soil, this material is expected to readily biodegrade. When released into the soil, this material is not expected to leach into groundwater. When released to water, this material is expected to quickly evaporate. When released into the water, this material is expected to have a half-life of less than 1 day. When released into water, this material is expected to readily biodegrade. This material has an estimated bioconcentration factor (BCF) of less than 100. This material is not expected to significantly bioaccumulate. When released into the air, this material is expected to be readily degraded by reaction with photochemically produced hydroxyl radicals. When released into the air, this material is expected to have a half-life of less than 1 day. When released into the air, this material may be removed from the atmosphere to a moderate extent by wet deposition.

## 13. DISPOSAL CONSIDERATIONS

Material that cannot be saved for recovery or recycling should be managed in an appropriate and approved waste facility. Processing, use or contamination of this product may change the waste management options. Waste generators must decide if discarded material is a hazardous waste. State and local disposal regulations may differ from federal disposal definitions found in 40 CFR 261.3. Dispose of container and unused contents in accordance with federal, state and local requirements.

## 14. TRANSPORT INFORMATION

US DOT, IATA, IMO

Proper Shipping Name: Di-n-butylamine

Hazard Class: 8(3)

UN Number: UN2248

Packing Group: II

Canada TDG

Additional Information: Flashpoint 47 C

## 15. REGULATORY INFORMATION

### US Federal Regulations:

TSCA: CAS#111-92-2 is listed on the TSCA Inventory.

Health and Safety Reporting List: CAS#111-92-2 not listed.

Chemical Test Rules: CAS#111-92-2 is not listed.

Section 12b: CAS#111-92-2 is not listed.

TSCA Significant New Use Rule: CAS#111-92-2 does not have an SNUR under TSCA.

CERCLA Hazardous Substances: CAS#111-92-2 – Does not have a final RQ

SARA Section 302: Does not have a TPQ

SARA Codes: CAS#111-92-2 – immediate, fire

Section 313: Dibutylamine (CAS# 111-92-2) is not subject to SARA Title III Section 313 and 40 CFR 373 reporting requirements.

Clean Air Act: CAS# 111-92-2 is not listed as a hazardous air pollutant (HAP). It is not a Class 1 Ozone Depleter. It is not a Class 2 Ozone Depleter.

Clean Water Act: CAS# 111-92-2 is listed as a Hazardous Substance. It is not a Priority Pollutant. It is not a Toxic Pollutant.

OSHA: Not considered highly hazardous by OSHA.

### US State Regulations:

CAS#111-92-2 is on the following state right-to-know lists: California, New Jersey, Pennsylvania, Minnesota, and Massachusetts

California Prop 65: California No Significant Risk Level: Not listed

### Canada:

DSL/NDSL: CAS#111-92-2 is listed on Canada's DSL list.

WHMIS: This product has a WHMIS classification of B3. This product has been classified in accordance with hazard criteria of the Controlled Products Regulations and this MSDS contains all the information required by those regulations.

### DSCL (EEC):

Hazard Symbols: F, C

Risk Phrases: R11 – Highly Flammable; R20/21/22 – Harmful by inhalation, in contact with skin, and if swallowed; R35 – Causes severe burns.

Safety Phrases: S3 – Keep in a cool place; S16 – Keep away from sources of ignition-no smoking; S26 – In case of contact with eyes, rinse immediately with plenty of water and seek medical advice; S29 – Do not empty into drains; S36/37/39: Wear suitable protective clothing, gloves, and eye/face protection; S45 – In case of accident, or if you feel unwell, seek medical advice immediately (show label where possible).

WGK (Water Danger/protection): CAS# 111-92-2: 1

## 16. OTHER INFORMATION

Originally Prepared: 6/18/2008

Last Revised: 12/1/2015 – Updated information for eye and face protection in Section 8.

The information contained herein is based on current knowledge and experience; no responsibility is accepted that the information is sufficient or correct in all cases. Users should consider these data only as a supplement to other information gathered by them and must make independent determinations of suitability and completeness of information from all sources to assure proper use and disposal of these materials and the safety and health of employees and customers and the protection of the environment.

TEDIA COMPANY, INC. MAKES NO REPRESENTATIONS OR WARRANTIES, EITHER EXPRESS OR IMPLIED, INCLUDING WITHOUT LIMITATION ANY WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE WITH RESPECT TO THE INFORMATION SET FORTH HEREIN OR THE PRODUCT TO WHICH THE

INFORMATION REFERS. ACCORDINGLY, TEDIA COMPANY, INC. WILL NOT BE RESPONSIBLE FOR DAMAGES RESULTING FROM USE OF OR RELIANCE UPON THIS INFORMATION.