

SAFETY DATA SHEET



1000 Tedia Way
Fairfield, Ohio 45014
USA
Email: tedia@tedia.com
Web: www.tedia.com

24-Hour Emergency Number (CHEMTREC)

USA: 800-424-9300
International: 703-527-3887

All non-emergency numbers should be directed
to Customer Service at 800-PURITY1

DIETHYLAMINE

SDS No. M0064

1. CHEMICAL PRODUCT AND COMPANY IDENTIFICATION

Product Name: Diethylamine

Synonyms: Ethanamine, N-Ethyl

Recommended Use: This product is recommended for laboratory and manufacturing use only. It is not recommended for drug, food or household use.

2. HAZARDS IDENTIFICATION



Classification:

Flammable Liquids: GHS Category 2

Acute Toxicity, Oral: GHS Category 4

Acute Toxicity, Inhalation: GHS Category 4

Acute Toxicity, Dermal: GHS Category 3

Skin Irritation: GHS Category 2

Eye Damage: GHS Category 1

Respiratory Sensitization: GHS Category 1

Skin Sensitization: GHS Category 1

Acute Aquatic Toxicity: GHS Category 3

Label Elements

Signal Word: DANGER!

Hazard Statements:

H225 - Highly flammable liquid and vapor.

H302 - Harmful if swallowed.

H311 - Toxic in contact with skin.

H315 - Causes skin irritation.

H317 - May cause an allergic skin reaction.

H318 - Causes serious eye damage.

H332 - Harmful if inhaled.

H334 - May cause allergy or asthma symptoms or breathing difficulties if inhaled.

H402 - Harmful to aquatic life.

Clear focus. Consistent results. Complete confidence.

Precautionary Statements:

- P210 – Keep away from heat/sparks/open flames/hot surfaces. – No smoking.
- P243 – Take precautionary measures against static discharge.
- P273 – Avoid release to the environment.
- P280 – Wear protective gloves/protective clothing/eye protection/face protection.
- P284 – Wear respiratory protection.
- P301+P310 – If SWALLOWED: Immediately call or POISON CENTER or a doctor/physician.
- P303+P361+P353 – If on skin or hair: Remove/take off immediately all contaminated clothing. Rinse skin with water/shower.
- P304+P312 – IF INHALED: Call a POISON CENTER or doctor/physician if you feel unwell.

Emergency Overview

May be fatal if swallowed, inhaled, or absorbed through the skin. Causes burns by all exposure routes. Highly flammable liquid or vapor. Vapor may cause flash fire. Target Organs: Eyes, skin, and mucous membranes.

HMIS Rating:

Health – 3* Flammability – 3 Physical Hazard – 0 PPE – User supplied

NOTE: HMIS ratings use a numbering scale that ranges from 0 - 4 to indicate the degree of hazard. A value of zero means the chemical presents no hazard while a value of four indicates a high hazard. These ratings are based on the inherent properties of this chemical under expected conditions of normal use and are not intended to be used in emergency situations. PPE is determined by the user based on their needs and conditions.

3. COMPOSITION AND INFORMATION ON INGREDIENTS

<u>Ingredient</u>	<u>CAS No</u>	<u>Percent</u>	<u>Hazardous</u>
Diethylamine	109-89-7	>99%	Yes

4. FIRST-AID MEASURES

Inhalation: If inhaled, remove to fresh air. If not breathing, begin artificial respiration, but DO NOT give mouth-to-mouth resuscitation. Get medical attention.

Ingestion: If swallowed, get medical attention immediately; DO NOT induce vomiting. Never give anything by mouth to an unconscious person. Rinse mouth with water.

Skin Contact: Immediately flush skin with plenty of water for at least 15 minutes while removing contaminated clothing and shoes. Get medical attention immediately. Discard contaminated clothing and shoes.

Eye Contact: Immediately flush eyes with plenty of water for at least 15 minutes, lifting lower and upper eyelids occasionally. Get medical attention immediately.

5. FIRE FIGHTING MEASURES

Flammability: Extremely flammable liquid and vapor (GHS Category 1)

Auto-ignition Temperature: Information not available.

Flash Point: -23° C (-9° F)

Flammable Limits: Lower Limit – 1.8 vol %, Upper Limit – 10.1 vol %

Products of Combustion: May decompose into toxic products under fire conditions (nitrogen oxides, carbon monoxide, carbon dioxide, amines).

Specific Fire Hazards: As in any fire, always wear self-contained breathing apparatus in pressure-demand (MSA/NIOSH approved or equivalent), and full protective gear. Use water spray to keep fire exposed containers cool. Approach fire from upwind to avoid hazardous vapors and toxic decomposition products. Vapors may cause flash fire. Vapors are heavier than air and may travel to a source of ignition and flash back. Vapors can spread along the ground and collect in low or confined areas.

Specific Explosion Hazards: None

Fire Fighting Media: For small fires, use dry chemical, carbon dioxide, water spray, or alcohol-resistant foam. Water may be ineffective.

National Fire Protective Association (Estimated): Health - 3, Flammability - 3, Reactivity - 0

NOTE: NFPA ratings use a numbering scale that ranges from 0 - 4 to indicate the degree of hazard. A value of zero means the chemical presents no hazard while a value of four indicates a high hazard. They are for use by emergency personnel to address the hazards that are presented by short term, acute exposure to this product under fire, spill, or similar emergencies. Ratings involve data and interpretations that may vary from company to company.

6. ACCIDENTAL RELEASE MEASURES

Absorb spilled liquid with sorbent pads, socks, or other inert material such as vermiculite, sand, or earth. Water can be used to create a non-flammable mixture. Provide ventilation to the affected area and remove all ignition sources. Approach the spill from upwind and pick up absorbed material and place it in a suitable container. Always use proper personal protective equipment as described in section 8.

7. HANDLING AND STORAGE

Precautions: Always use proper personal protective equipment as described in section 8. Wash thoroughly after handling. Ground and bond containers when transferring material. Avoid contact with eyes, skin, and clothing. Remove contaminated clothing and wash before reuse. Empty containers contain product residue (liquid and vapor) and can be dangerous. Keep container tightly closed and away from heat, spark, and flame. Do not pressurize, cut, weld, braze, solder, drill, grind, or expose empty containers to heat, sparks, or open flames. Use with adequate ventilation. Avoid breathing vapor or mist.

Storage: Keep in a flammables area away from all sources of ignition and oxidizing materials. Keep in a tightly closed container. Store in a cool, dry, well-ventilated area away from incompatible substances. Keep away from acids. Protect from moisture.

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Engineering Controls: Use explosion-proof ventilation equipment. Facilities storing or using the material should be equipped with eyewash station and a safety shower. Use adequate general or local exhaust ventilation to keep airborne concentrations below the permissible exposure limits.

Personal Protection: Wear protective chemical goggles or appropriate eye protection. Use appropriate protective gloves and protective clothing to prevent skin exposure. A respiratory protection program that meets OSHA 29 CFR 1910.134 and ANSI Z88.2 requirements or European Standard EN 149 must be followed whenever possible. Always use a NIOSH or European Standard EN 149 approved respirator when necessary.

Exposure Limits:

ACGIH – 5 ppm TWA; Skin – potential significant contribution to overall exposure by cutaneous route

NIOSH – 10 ppm TWA; 30 mg/m³ TWA; 200 ppm IDLH

OSHA Final PELs – 25 ppm TWA; 75 mg/m³ TWA

9. PHYSICAL AND CHEMICAL PROPERTIES

Physical State and Appearance: Clear, colorless liquid.

Odor: Fishy ammonia like odor

Odor Threshold: <1 ppm

Molecular Formula: (C₂H₅)₂NH

Molecular Weight: 73.13

Auto-ignition Temperature: Information not available.

Flash Point: -23° C (-9° F)

Flammable Limits: Lower Limit – 1.8 vol %, Upper Limit – 10.1 vol %

pH: Very alkaline.

Boiling Point: 55-58° C @ 760 mm Hg

Freezing/Melting Point: -50° C

Decomposition Temperature: Not available.

Specific Gravity: 0.71 g/cm³

Vapor Density (Air=1): 2.5

Vapor Pressure: 195 mm Hg @ 20° C.

Viscosity: Not available.

Solubility: Miscible in water.

Conductivity (-33.5°C): Conductive; Conductivity = 2.2×10^5 pS/m; Dielectric Constant = NA; Relaxation Time Constant = NA

10. STABILITY AND REACTIVITY

Stability: Stable under normal temperatures and pressures.

Conditions to Avoid: Ignition sources, excess heat.

Incompatibility With Various Substances: Aldehydes, Alcohols, Dicyanofurazan, Ketones, phenols, Acids, Halogenated hydrocarbon, Oxidizing agents, Epoxides.

Hazardous Decomposition Products: Nitrogen oxides, carbon monoxide, carbon dioxide, amines.

Hazardous Polymerization: Will not occur

11. TOXICOLOGICAL INFORMATION

Routes of Entry: Inhalation, skin absorption, skin contact

Acute Exposure Hazards:

INHALATION HAZARD: Cause burns in respiratory tract, coughing, and pulmonary edema. Animal studies with diethylamine have shown lung, liver, and heart damage from overexposure.

INGESTION HAZARD: Causes gastrointestinal tract burns. May be harmful if swallowed.

SKIN CONTACT HAZARD: Causes skin burns. May be absorbed through the skin in harmful amounts. Prolonged or repeated contact may dry the skin and cause irritation.

EYE CONTACT HAZARD: Causes eye burns. Vapor may cause eye irritation. A 10% aqueous solution caused severe eye burns in rabbits.

Chronic Exposure Hazards: Chronic exposure may produce effects similar to acute exposure.

Animal Toxicity:

Inhalation, rat: LC50 = 4000 ppm/4H;

Oral, mouse: LD50 = 500 mg/kg;

Oral, rat: LD50 = 540 mg/kg;

Skin, rabbit: LD50 = 577 uL/kg;

Carcinogenicity: Not listed as a carcinogen by ACGIH, IARC, NTP, or CA Prop 65

Epidemiology: Edema of the epithelium of the cornea, generally without pain, has been produced by amine vapors, causing colored halos to be seen around lights, usually in the evening, after industrial exposure to the vapors of various amines.

Teratogenicity: No information available.

Reproductive Effects: No information available.

Mutagenicity: No information available.

Neurotoxicity: No information available.

12. ECOLOGICAL INFORMATION

Ecotoxicity:

Fish: Rainbow Trout: LC50 = 25-198 mg/L, 96H

Water flea: Daphnia: EC50 = 56 mg/L, 48H

Algae: Green Algae: EC50 = 20 mg/L, 96H

Environmental Fate:

Readily biodegradable. An environmental hazard cannot be excluded in the event of unprofessional handling or disposal.

13. DISPOSAL CONSIDERATIONS

Material that cannot be saved for recovery or recycling should be managed in an appropriate and approved waste facility. Processing, use or contamination of this product may change the waste management options. Waste generators must

decide if discarded material is a hazardous waste. State and local disposal regulations may differ from federal disposal definitions found in 40 CFR 261.3. Dispose of container and unused contents in accordance with federal, state and local requirements.

14. TRANSPORT INFORMATION

US DOT

Proper Shipping Name: Diethylamine
Hazard Class: 3(8)
UN Number: UN1154
Packing Group: II

IMDG

Proper Shipping Name: Diethylamine
Hazard Class: 3(8)
UN Number: UN1154
Packing Group: II

IATA

Proper Shipping Name: Diethylamine
Hazard Class: 3(8)
UN Number: UN1154
Packing Group: II

15. REGULATORY INFORMATION

US Federal Regulations:

CERCLA Hazardous Substances: CAS#109-89-7 – 100 lb final RQ; 45.4 kg final RQ
SARA Section 302: Does not have a TPQ
SARA Codes: CAS#109-89-7 – acute, fire
Section 313: Diethylamine (CAS# 109-89-7) is not subject to SARA Title III Section 313 reporting requirements.
OSHA: Not considered highly hazardous by OSHA.

US State Regulations:

CAS#109-89-7 is on the following state right-to-know lists: New Jersey, Pennsylvania, and Massachusetts
California Prop 65: California No Significant Risk Level: Not listed

16. OTHER INFORMATION

Originally Prepared: 6/18/2008

Last Revised: 9/9/2014 – Updated pictograms, hazard classification, hazard statements, and precautionary statements in Section 2. First aid measures updated in Section 4. Environmental information updated in Section 12. Transportation information updated in Section 14

The information contained herein is based on current knowledge and experience; no responsibility is accepted that the information is sufficient or correct in all cases. Users should consider these data only as a supplement to other information gathered by them and must make independent determinations of suitability and completeness of information from all sources to assure proper use and disposal of these materials and the safety and health of employees and customers and the protection of the environment.

TEDIA COMPANY, INC. MAKES NO REPRESENTATIONS OR WARRANTIES, EITHER EXPRESS OR IMPLIED, INCLUDING WITHOUT LIMITATION ANY WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE WITH RESPECT TO THE INFORMATION SET FORTH HEREIN OR THE PRODUCT TO WHICH THE

INFORMATION REFERS. ACCORDINGLY, TEDIA COMPANY, INC. WILL NOT BE RESPONSIBLE FOR DAMAGES RESULTING FROM USE OF OR RELIANCE UPON THIS INFORMATION.