

SAFETY DATA SHEET



1000 Tedia Way
Fairfield, Ohio 45014
USA
Email: tedia@tedia.com
Web: www.tedia.com

24-Hour Emergency Number (CHEMTREC)

USA: 800-424-9300

International: 703-527-3887

All non-emergency numbers should be directed
to Customer Service at 800-PURITY1

PIPERIDINE

SDS No. M0171

1. CHEMICAL PRODUCT AND COMPANY IDENTIFICATION

Product Name: Piperidine

Synonyms: Hexahydropyridine; Azacyclohexane; Cyclopentimine; Hexazine

Recommended Use: This product is recommended for laboratory and manufacturing use only. It is not recommended for drug, food or household use.

2. HAZARDS IDENTIFICATION



Classification:

Flammable Liquids: GHS Category 2

Acute Toxicity, Oral: GHS Category 4

Acute Toxicity, Inhalation: GHS Category 3

Acute Toxicity, Dermal: GHS Category 3

Skin Corrosion: GHS Category 1B

Serious Eye Damage: GHS Category 1

Acute Aquatic Toxicity: GHS Category 3

Chronic Aquatic Toxicity: GHS Category 3

Label Elements

Signal Word: DANGER!

Hazard Statements:

H225 – Highly flammable liquid and vapor

H302 – Harmful if swallowed.

H311 – Toxic in contact with skin.

H314 – Causes severe skin burns and eye damage.

H331 – Toxic if inhaled.

H361 – Suspected of damaging fertility or the unborn child.

Precautionary Statements:

P210 – Keep away from heat, hot surface, sparks, open flames and other ignition sources. - No smoking.

P240 – Ground/bond container and receiving equipment.

Clear focus. Consistent results. Complete confidence.

- P243 – Take precautionary measures against static discharge.
 P260 – Do not breathe dust/ fume/ gas/ mist/ vapors/ spray.
 P271 – Use only outdoors or in a well-ventilated area.
 P280 – Wear protective gloves/ protective clothing/ eye protection/ face protection.
 P301+P330+P331 – IF SWALLOWED: Rinse mouth. Do NOT induce vomiting.
 P303+P361+P353 – IF ON SKIN (or hair): Take off Immediately all contaminated clothing. Rinse SKIN with water [or shower].
 P304+P340 – IF INHALED: Remove person to fresh air and keep comfortable for breathing.
 P305+P351+P338 – IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses if present and easy to do - continue rinsing.
 P403+P233 – Store in a well-ventilated place. Keep container tightly closed.
 P405 – Store locked up.
 P501 – Dispose of contents/ container to an approved waste disposal plant.

Emergency Overview

Causes severe burns by all exposure routes. Harmful if inhaled or absorbed through the skin. Highly flammable liquid and vapor.

HMIS Rating:

Health – 3 Flammability – 3 Physical Hazard – 0 PPE – User supplied

NOTE: HMIS ratings use a numbering scale that ranges from 0 - 4 to indicate the degree of hazard. A value of zero means the chemical presents no hazard while a value of four indicates a high hazard. These ratings are based on the inherent properties of this chemical under expected conditions of normal use and are not intended to be used in emergency situations. PPE is determined by the user based on their needs and conditions.

3. COMPOSITION AND INFORMATION ON INGREDIENTS

<u>Ingredient</u>	<u>CAS No</u>	<u>Percent</u>	<u>Hazardous</u>
Piperidine	110-89-4	>98%	Yes

4. FIRST-AID MEASURES

Inhalation: Get medical aid immediately. Remove from exposure and move to fresh air immediately. If breathing is difficult, give oxygen. Do not use mouth-to-mouth resuscitation if victim ingested or inhaled the substance; induce artificial respiration with the aid of a pocket mask equipped with a one-way valve or other proper respiratory medical device.

Ingestion: Do not induce vomiting. If victim is conscious and alert rinse mouth with water. Never give anything by mouth to an unconscious person. Get medical aid immediately.

Skin Contact: Get medical aid immediately. Flush skin with plenty of water for at least 15 minutes while removing contaminated clothing and shoes. Discard contaminated clothing in a manner which limits further exposure. Destroy contaminated shoes.

Eye Contact: Get medical aid immediately. Do NOT allow victim to rub eyes or keep eyes closed. Gently lift eyelids and flush continuously with water. Extensive irrigation with water is required (at least 30 minutes).

Notes to Physician: Treat symptomatically and supportively.

5. FIRE FIGHTING MEASURES

Flammability: Highly flammable liquid and vapor (GHS Category 2)

Auto-ignition Temperature: 320° C (608° F)

Flash Point: 16° C (60.8° F)

Flammable Limits: Lower Limit – Not available, Upper Limit – Not available.

Products of Combustion: Will decompose into irritating fumes and gases, nitrogen oxides, nitrogen gas, carbon monoxide, and carbon dioxide under fire conditions.

Specific Fire Hazards: As in any fire, wear a self-contained breathing apparatus in pressure-demand, MSHA/NIOSH (approved or equivalent), and full protective gear. Vapors may form an explosive mixture with air. Vapors can travel to a

source of ignition and flash back. During a fire, irritating and highly toxic gases may be generated by thermal decomposition or combustion. Flammable Liquid. Can release vapors that form explosive mixtures at temperatures above the flashpoint. Use water spray to keep fire-exposed containers cool. Water may be ineffective. Material is lighter than water and a fire may be spread by the use of water. Vapor may explode if ignited in a confined area. Vapors may be heavier than air. They can spread along the ground and collect in low or confined areas.

Specific Explosion Hazards: May polymerize explosively when involved in a fire. Containers may explode when heated.

Fire Fighting Media: For small fires, use dry chemical, carbon dioxide, water spray or alcohol-resistant foam. Do NOT get water inside containers. For large fires, use water spray, fog or alcohol-resistant foam. Do NOT use straight streams of water. Cool containers with flooding quantities of water until well after fire is out.

National Fire Protective Association: Health - 3, Flammability - 3, Reactivity - 0

NOTE: NFPA ratings use a numbering scale that ranges from 0 - 4 to indicate the degree of hazard. A value of zero means the chemical presents no hazard while a value of four indicates a high hazard. They are for use by emergency personnel to address the hazards that are presented by short term, acute exposure to this product under fire, spill, or similar emergencies. Ratings involve data and interpretations that may vary from company to company.

6. ACCIDENTAL RELEASE MEASURES

Avoid runoff into storm sewers and ditches which lead to waterways. Clean up spills immediately, observing precautions in the Protective Equipment section. Cover with sand, dry lime or soda ash and place in a closed container for disposal. Remove all sources of ignition. Provide ventilation. Always use proper personal protective equipment as described in section 8.

7. HANDLING AND STORAGE

Precautions: Wash thoroughly after handling. Wash thoroughly after handling. Remove contaminated clothing and wash before reuse. Ground and bond containers when transferring material. Do not get in eyes, on skin, or on clothing. Empty containers retain product residue, (liquid and/or vapor), and can be dangerous. Do not ingest or inhale. Use only in a chemical fume hood. Discard contaminated shoes. Do not pressurize, cut, weld, braze, solder, drill, grind, or expose empty containers to heat, sparks or open flames.

Storage: Keep away from heat, sparks, and flame. Store in a cool, dry, well-ventilated area away from incompatible substances. Keep away from strong acids. Flammables-area. Corrosives area.

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Engineering Controls: Use explosion-proof ventilation equipment. Facilities storing or using the material should be equipped with eyewash station and a safety shower. Use adequate general or local exhaust ventilation to keep airborne concentrations below the permissible exposure limits.

Personal Protection: Wear protective chemical goggles and face shield for eye and face protection. Use appropriate protective gloves and protective clothing to prevent skin exposure. A respiratory protection program that meets OSHA 29 CFR 1910.134 and ANSI Z88.2 requirements or European Standard EN 149 must be followed whenever possible. Always use a NIOSH or European Standard EN 149 approved respirator when necessary.

Exposure Limits:

ACGIH – None

NIOSH – None

OSHA Final PELs – None

AIHA WEL – 1 ppm (3.5 md/m³) skin

9. PHYSICAL AND CHEMICAL PROPERTIES

Physical State and Appearance: Clear to slight yellow liquid.

Odor: pepper-like odor

Molecular Formula: (CH₂)₅NH

Molecular Weight: 85.15

Auto-ignition Temperature: 320° C (608° F)

Flash Point: 16° C (60.8° F)

Flammable Limits: Lower Limit – Not available, Upper Limit – Not available.

pH: 12.6.

Boiling Point: 106° C @ 760 mm Hg

Freezing/Melting Point: -13° C

Decomposition Temperature: 500° C

Specific Gravity: 0.8622 g/cm³ @ 20° C

Vapor Density (Air=1):3.0

Vapor Pressure: 40 mm Hg @ 29.9° C.

Evaporation Rate (Butyl acetate = 1): Not available

Viscosity: 1.46 mPa 20° C

Solubility: Completely miscible in water

Conductivity at 25°C: Conductive; Conductivity = 2×10^4 pS/m; Dielectric Constant = NA; Relaxation Time Constant = NA

10. STABILITY AND REACTIVITY

Stability: Stable under normal temperatures and pressures.

Conditions to Avoid: Incompatible materials, ignition sources, excess heat.

Incompatibility With Various Substances: Strong oxidizing agents; dicyanofurazan; N-nitrosoacetanilide; 1-Perchlorylpiperidine .

Hazardous Decomposition Products: Carbon monoxide, carbon dioxide, nitrogen oxides, nitrogen gas.

Hazardous Polymerization: Has not been reported.

11. TOXICOLOGICAL INFORMATION

Routes of Entry: Inhalation, skin absorption, skin contact

Acute Exposure Hazards:

INHALATION HAZARD: May cause severe irritation of the respiratory tract with sore throat, coughing, shortness of breath and delayed lung edema. Causes chemical burns to the respiratory tract. May cause effects similar to those described for ingestion. Damage may be delayed. May cause bronchial pneumonia.

INGESTION HAZARD: Harmful if swallowed. May cause severe and permanent damage to the digestive tract. Causes gastrointestinal tract burns. Can cause nervous system damage. May cause tremors and convulsions.

SKIN CONTACT HAZARD: Harmful if absorbed through the skin. May be absorbed through the skin. If absorbed, causes symptoms similar to those of ingestion. Penetration may continue for several days. Causes severe skin irritation and burns.

EYE CONTACT HAZARD: Contact with liquid or vapor causes severe burns and possible irreversible eye damage. Contact may cause ulceration of the conjunctiva and cornea. Eye damage may be delayed. May cause conjunctivitis. May cause blindness.

Chronic Exposure Hazards: Repeated inhalation may cause chronic bronchitis. Prolonged or repeated contact may cause skin necrosis and/or ulceration of the skin. May cause chronic cough.

Animal Toxicity:

Draize test, rabbit, eye: 250 ug/24H Severe;

Draize test, rabbit, skin: 5 mg/24H Severe;

Inhalation, mouse: LC50 = 6000 mg/m³/2H;

Oral, mouse: LD50 = 30 mg/kg;

Oral, rabbit: LD50 = 145 mg/kg;

Oral, rat: LD50 = 400 mg/kg;

Skin, rabbit: LD50 = 276 mg/kg;

Carcinogenicity: Not listed as a carcinogen by ACGIH, IARC, NTP, or CA Prop 65

Epidemiology: No information found.

Teratogenicity: No information found.

Reproductive Effects: Inhalation, Rat: TClO = 3 mg/m³/24H - fetotoxic effects. Inhalation, rat: TClO = 100 mg/m³/24H - effected litter size.

Mutagenicity: Mutagenic at 5050 æmol/L in mouse lymphocyte.

Neurotoxicity: Intravenous, rabbit: LDLo = 160 mg/kg. Caused spastic paralysis and convulsions or effect on seizure threshold.

12. ECOLOGICAL INFORMATION

Ecotoxicity: No data available.

Environmental Fate: No data available.

13. DISPOSAL CONSIDERATIONS

Material that cannot be saved for recovery or recycling should be managed in an appropriate and approved waste facility. Processing, use or contamination of this product may change the waste management options. Waste generators must decide if discarded material is a hazardous waste. State and local disposal regulations may differ from federal disposal definitions found in 40 CFR 261.3. Dispose of container and unused contents in accordance with federal, state and local requirements.

14. TRANSPORT INFORMATION

US DOT

Proper Shipping Name: Piperidine

Hazard Class: 8 (3)

UN Number: UN2401

Packing Group: I

IMDG

Proper Shipping Name: Piperidine

Hazard Class: 8 (3)

UN Number: UN2401

Packing Group: I

IATA

Proper Shipping Name: Piperidine

Hazard Class: 8 (3)

UN Number: UN2401

Packing Group: I

15. REGULATORY INFORMATION

US Federal Regulations:

CERCLA Hazardous Substances: CAS# 110-89-4 does not have a RQ

SARA Section 302: CAS# 110-89-4 TPQ: 1000 lbs

SARA Codes: CAS# 110-89-4 – immediate, fire

Section 313: Not reportable.

OSHA: Not considered highly hazardous by OSHA.

US State Regulations:

CAS# 110-89-4 is on the following state right-to-know lists: New Jersey, Pennsylvania, and Massachusetts.

California Prop 65: This product contains no chemicals known to the State of California to cause cancer, birth defects, or any other reproductive harm.

16. OTHER INFORMATION

Originally Prepared: 12/11/2007

Last Revised: 04/15/2019 – Updated GHS pictograms, GHS precautionary and hazard statements, and firstaid.

The information contained herein is based on current knowledge and experience; no responsibility is accepted that the information is sufficient or correct in all cases. Users should consider these data only as a supplement to other information gathered by them and must make independent determinations of suitability and completeness of information from all sources to assure proper use and disposal of these materials and the safety and health of employees and customers and the protection of the environment.

TEDIA COMPANY, INC. MAKES NO REPRESENTATIONS OR WARRANTIES, EITHER EXPRESS OR IMPLIED, INCLUDING WITHOUT LIMITATION ANY WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE WITH RESPECT TO THE INFORMATION SET FORTH HEREIN OR THE PRODUCT TO WHICH THE INFORMATION REFERS. ACCORDINGLY, TEDIA COMPANY, INC. WILL NOT BE RESPONSIBLE FOR DAMAGES RESULTING FROM USE OF OR RELIANCE UPON THIS INFORMATION.